


Silverpod^{PRO}

Water-based Bulk Air Cargo Pallet Shippers

Silverpod PRO pallet shippers will comfortably maintain the designated temperature for a range of transport modes and extended durations.

The patented design of Silverpod PRO provides overall cost reductions in packaging, freight and warehousing, providing optimized payload capacity and cost-effective integration with the world's freight networks.



Key Features



Designed to accept loose and palletized consignments



US and Euro pallet footprint options available



Patented design



Up to 120 hours of thermal protection



Supplied flat packed for cost-effective delivery and storage




One-size coolants fit all pallet shipper sizes



Easy packing and conditioning



Globally available via extensive supply network



PAYLOAD (LITERS)
100-2994



TEMPERATURE RANGE
+2°C to +8°C
+15°C to +25°C
+2°C to +30°C
-20°C



DURATION (HOURS)
96-180

SIZE	PAYLOAD	TEMPERATURE RANGE	DURATION	INTERNAL SPACE L x W x H	EXTERNAL DIMENSIONS L x W x H	TARE WEIGHT
Silverpod PRO Narrow Body Aircraft	135 L 4.76 cu ft	+2°C to +8°C	120 hrs	900 x 500 x 300 mm 35.43 x 19.68 x 11.81 in	1200 x 800 x 710 mm 47.24 x 31.49 x 27.95 in	61 kg 134.5 lbs
		+15°C to +25°C	120 Summer hrs 96 Winter hrs			
	100 L 3.53 cu ft	-20°C	180 hrs	900 x 500 x 222 mm 35.43 x 19.68 x 8.74 in	11 kg 24.25 lbs	
Silverpod PRO Small	264 L 9.32 cu ft	+2°C to +8°C	120 hrs	880 x 480 x 625 mm 43.64 x 18.89 x 24.60 in	1200 x 800 x 1080 mm 47.24 x 31.49 x 42.51 in	100 kg 220 lbs
		+15°C to +25°C				
	288 L 10.17 cu ft	-20°C		908 x 508 x 625 mm 35.74 x 20.00 x 24.60 in		34 kg 75 lbs
Silverpod PRO Medium	485 L 17.12 cu ft	+2°C to +8°C	120 hrs	880 x 680 x 810 mm 43.64 x 26.77 x 31.88 in	1200 x 1000 x 1260 mm 47.24 x 39.37 x 49.60 in	135 kg 297.6 lbs
		+15°C to +25°C				
	539 L 19.03 cu ft	-20°C		922 x 722 x 810 mm 36.29 x 28.42 x 31.88 in		41 kg 90.4 lbs
Silverpod PRO Large	661 L 23.34 cu ft	+2°C to +8°C	120 hrs	880 x 680 x 1105 mm 43.64 x 26.77 x 43.50 in	1200 x 1000 x 1550 mm 47.24 x 39.37 x 61.02 in	160 kg 352.7 lbs
		+15°C to +25°C				
	717 L 25.32 cu ft	-20°C		932 x 732 x 1052 mm 36.69 x 28.81 x 41.41 in		47 kg 103.6 lbs
Silverpod PRO LD7 Quarter PMC	1195 L 42.2 cu ft	+2°C to +8°C	120 hrs	1225 x 856 x 1140 mm 48.22 x 33.70 x 44.88 in	1565 x 1196 x 1570 mm 61.61 x 47.08 x 61.81 in	227 kg 500.5 lbs
		+15°C to +25°C				
Silverpod PRO Single	1524 L 53.81 cu ft	+2°C to +8°C	120 hrs	1250 x 1060 x 1150 mm 49.21 x 41.73 x 45.27 in	1565 x 1375 x 1560 mm 61.61 x 54.13 x 61.41 in	198 kg 436.5 lbs
		+15°C to +25°C				
	1572 L 55.51 cu ft	-20°C		1302 x 1112 x 1086 mm 51.25 x 43.77 x 42.75 in		52 kg 114.6 lbs
Silverpod PRO LD7 Half PAG	2702 L 95.42 cu ft	+2°C to +8°C	120 hrs	1880 x 1250 x 1150 mm 74.01 x 49.21 x 45.27 in	2195 x 1565 x 1590 mm 86.41 x 61.61 x 62.59 in	360 kg 793.6 lbs
		+15°C to +25°C				
Silverpod PRO LD7 Half PMC	2994 L 105.73 cu ft	+2°C to +8°C	120 hrs	2083 x 1250 x 1150 mm 82.00 x 49.21 x 45.27 in	2398 x 1565 x 1590 mm 94.40 x 61.61 x 62.59 in	370 kg 815.7 lbs
		+15°C to +25°C				
Silverpod PRO Ambi+shield Euro/Low Level	647 L 22.84 cu ft	+2°C to +30°C	96 hrs	1225 x 825 x 640 mm 48.23 x 32.48 x 25.2 in	1295 x 895 x 890 mm 50.98 x 35.24 x 35.04 in	13 kg 28.66 lbs
Silverpod PRO Ambi+shield Euro	1354 L 47.81 cu ft	+2°C to +30°C	96 hrs	1225 x 825 x 1340 mm 48.23 x 32.48 x 52.76 in	1295 x 895 x 1590 mm 50.98 x 35.24 x 62.6 in	15 kg 33.07 lbs
Silverpod PRO Ambi+shield US	1748 L 61.73 cu ft	+2°C to +30°C	96 hrs	1249 x 1046 x 1338 mm 49.17 x 41.2 x 52.68 in	1335 x 1132 x 1590 mm 52.56 x 44.57 x 62.6 in	20 kg 44.09 lbs

Contact us at passivesolutions@csafeglobal.com

CSafe has a worldwide network of comprehensive service centers, manufacturing facilities, sales offices and local hub sites to provide solutions where and when you need them. With representatives across the Americas, EMEA and APAC, local and regional support is always available.