



SoftboxPRO

Single-Use Parcel Shippers

Softbox PRO is a well-established range of single-use, water-based, temperature-controlled parcel shippers which are used extensively by the pharmaceutical and logistics industries.

These parcel shippers enable quick and easy packing due to the use of thermal barriers which prevent the risk of cold shock in transit.

Softbox PRO has been an industry-leading single-use product for over ten years and offers cost-effectiveness and simplicity in use.



Key Features



Single-use water-based parcel shippers



+2°C to +8°C, +15°C to +25°C, -20°C and -60°C temperature options available



Cost-effective parcel solutions, especially for express networks



Up to 120 hours of qualified thermal protection



Easy to condition



Industry-leading Pharma-cool refrigerants



Molded insulated configuration enables quick and easy assembly



Globally available via extensive supply network



PAYLOAD (LITERS)
7–84



TEMPERATURE RANGE
+2°C to +8°C
+15°C to +25°C
-20°C
-60°C



DURATION (HOURS)
48–390

PRODUCT NAME	PAYLOAD	TEMPERATURE RANGE	DURATION	INTERNAL SPACE L x W x H	EXTERNAL DIMENSIONS L x W x H	TARE WEIGHT
Softbox PRO 7-48	7 L 0.24 cu ft	+2°C to +8°C	48 hrs	260 x 134 x 208 mm 10.23 x 5.27 x 8.18 in	453 x 413 x 415 mm 17.83 x 16.25 x 16.33 in	8.6 kg 18.95 lbs
		+15°C to +25°C				
Softbox PRO 7-120	7 L 0.24 cu ft	+2°C to +8°C	120 hrs	260 x 134 x 208 mm 10.23 x 5.27 x 8.18 in	598 x 458 x 454 mm 23.54 x 18.03 x 17.87 in	20.7 kg 45.63 lbs
		+15°C to +25°C				
Softbox PRO 13-48	13 L 0.45 cu ft	+2°C to +8°C	48 hrs	280 x 182 x 260 mm 11.01 x 7.16 x 10.23 in	483 x 456 x 487 mm 19.01 x 17.95 x 19.17 in	12.2 kg 26.89 lbs
		+15°C to +25°C				
Softbox PRO 13-120	13 L 0.45 cu ft	+2°C to +8°C	120 hrs	280 x 182 x 260 mm 11.01 x 7.16 x 10.23 in	643 x 528 x 520 mm 25.31 x 20.78 x 20.47 in	25.2 kg 55.55 lbs
		+15°C to +25°C				
Softbox PRO 28-48	28 L 0.98 cu ft	+2°C to +8°C	48 hrs	385 x 285 x 250 mm 15.15 x 11.22 x 9.84 in	578 x 563 x 477 mm 22.75 x 22.16 x 18.77 in	16.9 kg 37.25 lbs
		+15°C to +25°C				
Softbox PRO 28-120	28 L 0.98 cu ft	+2°C to +8°C	120 hrs	385 x 285 x 250 mm 15.15 x 11.22 x 9.84 in	748 x 648 x 523 mm 29.44 x 25.51 x 20.59 in	35.1 kg 77.38 lbs
		+15°C to +25°C				
Softbox PRO 60	60 L 2.11 cu ft	+2°C to +8°C	120 hrs	450 x 300 x 450 mm 17.71 x 11.81 x 17.71 in	782 x 632 x 875 mm 30.78 x 24.88 x 34.44 in	45 kg 99.20 lbs
		+15°C to +25°C	96 hrs			
Softbox PRO F24	22.4 L 0.79 cu ft	-20°C	153 hrs	337 x 297 x 224 mm 13.3 x 11.7 x 8.8 in	453 x 413 x 415 mm 17.8 x 16.3 x 16.3 in	1.92 kg 4.2 lbs
		-60°C	149 hrs			
Softbox PRO F39	34.6 L 1.22 cu ft	-20°C	245 hrs	366 x 336 x 281 mm 14.4 x 13.2 x 11.1 in	483 x 456 x 487 mm 19 x 18 x 19.2 in	2.34 kg 5.1 lbs
		-60°C	227 hrs			
Softbox PRO F43	40.7 L 1.44 cu ft	-20°C	247 hrs	459 x 319 x 278 mm 18.1 x 12.6 x 10.9 in	598 x 458 x 454 mm 23.5 x 18 x 17.9 in	2.68 kg 5.9 lbs
		-60°C	238 hrs			
Softbox PRO F64	58.7 L 2.07 cu ft	-20°C	278 hrs	460 x 446 x 286 mm 18.1 x 17.6 x 11.3 in	578 x 563 x 477 mm 22.8 x 22.2 x 18.8 in	3.42 kg 7.5 lbs
		-60°C	267 hrs			
Softbox PRO F101	84.3 L 2.977 cu ft	-60°C	390 hrs	611 x 507 x 272 mm 24.055 x 19.96 x 10.70 in	748 x 648 x 523 mm 29.44 x 25.5 x 20.59 in	4.94 kg 10.89 lbs

Contact us at passivesolutions@csafeglobal.com

CSafe has a worldwide network of comprehensive service centers, manufacturing facilities, sales offices and local hub sites to provide solutions where and when you need them. With representatives across the Americas, EMEA and APAC, local and regional support is always available.