Multi-Pallet Active Temperature-Controlled Container

Offering the largest payload capacity in the industry, the CSafe RAP leverages the groundbreaking heating and compressor-driven cooling technologies of the CSafe RKN with advanced VIP insulation to eliminate thermal risks to cargo traveling through extreme ambient temperature conditions on long-duration shipments.



Key Features





PAYLOAD (CUBIC METERS) 6.68



TEMPERATURE RANGE +2°C to +8°C +15°C to +25°C



DURATION (HOURS)


Technical Specifications


PRODUCT NAME	PAYLOAD	TEMPERATURE RANGE	DURATION	INTERNAL SPACE L x W x H	EXTERNAL DIMENSIONS L x W x H	TARE WEIGHT	MAXIMUM PAYLOAD WEIGHT	MAXIMUM ALLOWABLE WEIGHT
CSafe RAP	6.68 m³ 236 cu ft	+2°C to +8°C	120+ hrs	2477 x 2083 x 1295 mm 97.5 × 82 × 51 in	3175 x 2235 x 1626 mm 125 x 88 x 64 in	1213 kg 2675 lbs	4819 kg 10625 lbs	6033 kg 13300 lbs
		+15°C to +25°C						

Power Features

- Power sources:
 - AC power (100-240 V, 50-60 Hz)
 - Internal batteries (regulatory approved, sealed, nonspillable design that meets Dangerous Goods Regulations)

- Rechargeable anywhere in the world with included multisystem charging cables
- Rapid battery charging, from 0% to 100% in only 10 hours
- Run time >120 hours for typical shipments





Contact us at sales@csafeglobal.com

CSafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. CSafe and the logo designs presented in this material are trademarks or registered trademarks of CSafe. ©2024 CSafe

