



PCM Single-Use Parcel Shippers

Softbox® MAX incorporates advanced phase change material (PCM) refrigerants and TIF panels to ensure thermal protection in extreme conditions. Bringing together the optimal combination of thermal packaging and PCM creates a high-performance and temperature-stable environment of up to 96 hours.

The result is a lighter shipper, more payload space, and a high payload-to-weight ratio, enabling cost-effective transportation.



Key Features



Single-use PCM parcel shipper



Qualified to ISTA 7D test profiles



Easy-to-condition



48-96 hours of qualified thermal protection



Next generation recyclable Pharmacoool MAX PCM refrigerants



Simple configuration enables quick and easy packing



Globally available in three commonly used sizes



High payload-to-weight ratio minimizes shipping cost



PAYLOAD (LITERS)
4-22



TEMPERATURE RANGE
+2°C to +8°C
+15°C to +25°C



DURATION (HOURS)
48-96

Technical Specifications

PRODUCT NAME	PAYLOAD	TEMPERATURE RANGE	DURATION	INTERNAL SPACE L x W x H	EXTERNAL DIMENSIONS L x W x H	TARE WEIGHT
Softbox MAX 4L	4 L 0.14 cu ft	+2°C to +8°C	48-96 hrs	160 x 160 x 160 mm 6.29 x 6.29 x 6.29 in	370 x 370 x 390 mm 14.56 x 14.56 x 15.35 in	7 kg 15.43 lbs
		+15°C to +25°C				
Softbox MAX 11L	11 L 0.38 cu ft	+2°C to +8°C	48-96 hrs	222 x 222 x 222 mm 8.74 x 8.74 x 8.74 in	425 x 425 x 450 mm 16.73 x 16.73 x 17.71 in	10 kg 22.05 lbs
		+15°C to +25°C				
Softbox MAX 22L	22 L 0.77 cu ft	+2°C to +8°C	48-96 hrs	280 x 280 x 280 mm 11.02 x 11.02 x 11.02 in	480 x 480 x 500 mm 18.89 x 18.89 x 19.68 in	13 kg 28.66 lbs
		+15°C to +25°C				

Note: Softbox MAX products are not available in the United States

Contact us at sales@csafeglobal.com

Csafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. Csafe and the logo designs presented in this material are trademarks or registered trademarks of Csafe. ©2024 Csafe