



High-Performance Reusable Parcel Shippers

Softbox® VIP shippers with Vacuum Insulated Panel (VIP) technology, assure greater peace of mind in your cold chain, delivering optimal temperature-management performance and versatility for the safe transport of vital life science products to distribution centers, healthcare facilities and patients.

With pre-qualified configurations in four temperature ranges, two durations and six payload sizes, Softbox VIP reusable shippers offer a simplified packout process, hibernation capability and an industry-leading retest and reuse program.



Key Features



High-performance reusable solution




Qualified against ISTA 7D summer and winter profiles



Best-in-class VIP insulation for optimal thermal protection



50% longer shipment durations*



Simplified pack-out process with minimal components



Eliminates need for additional packing materials



Industry-leading reuse and requalification program



Globally available via extensive supply network

*Confirmed against market-leading solution at third-party testing facility.



PAYLOAD (LITERS)
5-56



TEMPERATURE RANGE
+2°C TO +8°C
+15°C TO +25°C
-25°C TO -15°C
< -60°C
< -70°C



DURATION (HOURS)
96-240+

Technical Specifications

PRODUCT NAME	PAYLOAD	TEMPERATURE RANGE	DURATION	INTERNAL SPACE L x W x H	EXTERNAL DIMENSIONS L x W x H	EXTERNAL DIMENSIONS (WITH TRACKER) L x W x H	TARE WEIGHT
Softbox VIP 5L	5 L 0.17 cu ft	+2°C to +8°C	96 hrs	177.8 x 177.8 x 177.8 mm 7 x 7 x 7 in	355.6 x 311.1 x 330.2 mm 14 x 12.25 x 13 in	355.6 x 311.1 x 362 mm 14 x 12.25 x 14.25 in	9.53 kg 21 lbs
			120 hrs				10.9 kg 24 lbs
		+15°C to +25°C	96 hrs				8.8 kg 19.5 lbs
			120 hrs				10.9 kg 22.50 lbs
		< -60°C*	120 hrs				15.9 kg 35 lbs
Softbox VIP 8L	8 L 0.28 cu ft	+2°C to +8°C	96 hrs	203.2 x 203.2 x 203.2 mm 8 x 8 x 8 in	381 x 336.55 x 355.6 mm 15 x 13.25 x 14 in	381 x 336.55 x 387.4 mm 15 x 13.25 x 15.25 in	11.3 kg 25 lbs
			120 hrs				13.2 kg 29.10 lbs
		+15°C to +25°C	96 hrs				11.1 kg 24.50 lbs
			120 hrs				12.5 kg 27.50 lbs
		< -60°C*	120 hrs				5 kg 11 lbs
Softbox VIP 14L	14 L 0.49 cu ft	< -70°C	240 hrs	250 x 250 x 246 mm 9.84 x 9.84 x 9.69 in	533 x 467 x 489 mm 20.98 x 18.38 x 19.52 in	n/a	14.9 kg 33 lbs
Softbox VIP 16L	16 L 0.57 cu ft	+2°C to +8°C	96 hrs	254 x 254 x 254 mm 10 x 10 x 10 in	431.8 x 387.35 x 406.4 mm 17 x 15.25 x 16 in	431.8 x 387.35 x 438.2 mm 17 x 15.25 x 17.25 in	13.8 kg 30.50 lbs
			120 hrs				15.2 kg 33.50 lbs
		+15°C to +25°C	96 hrs				13.2 kg 29.10 lbs
			120 hrs				15.2 kg 33.50 lbs
		< -60°C*	120 hrs				20 kg 44 lbs
Softbox VIP 35L	35 L 1.23 cu ft	+2°C to +8°C	96 hrs	330.2 x 330.2 x 330.2 mm 13 x 13 x 13 in	508 x 463.5 x 482.6 mm 20 x 18.25 x 19 in	508 x 463.5 x 514.4 mm 20 x 18.25 x 20.25 in	20.2 kg 44.50 lbs
			120 hrs				22.9 kg 50.5 lbs
		+15°C to +25°C	96 hrs				20.2 kg 44.50 lbs
			120 hrs				20.9 kg 46 lbs
		< -60°C*	120 hrs				27.7 kg 61 lbs
Softbox VIP 56L	56 L 1.98 cu ft	+2°C to +8°C	120 hrs	381 x 381 x 381 mm 15 x 15 x 15 in	559 x 502 x 533.5 mm 22 x 19.75 x 21 in	559 x 502 x 565.2 mm 22 x 19.75 x 22.5 in	10 kg 22 lbs
		-25°C to -15°C					30.4 kg 67 lbs
		< -60°C*					33.1 kg 73 lbs
							17.3 kg 38 lbs

*-70°C test data available upon request
**96 hr durations not available in APAC region

Contact us at sales@csafeglobal.com

CSafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. CSafe and the logo designs presented in this material are trademarks or registered trademarks of CSafe. ©2024 CSafe