

High-Performance Reusable Parcel Shipper

Softbox® VIP shippers with Vacuum Insulated Panel (VIP) technology, assure greater peace of mind in your cold chain, delivering optimal temperature-management performance and versatility for the safe transport of vital life science products to distribution centers, healthcare facilities and patients.

With pre-qualified configurations in four temperature ranges, two durations and six payload sizes, Softbox VIP reusable shippers offer a simplified packout process, hibernation capability and an industry-leading retest and reuse program.



Key Features

 <p>High-performance reusable solution</p>	 <p>Qualified against ISTA 7D summer and winter profiles</p>	 <p>Best-in-class VIP insulation for optimal thermal protection</p>	 <p>Industry-leading reuse and requalification program</p>
 <p>Simplified pack-out process with minimal components</p>	 <p>Eliminates need for additional packing materials</p>	 <p>50% longer shipment durations*</p>	 <p>Globally available via extensive supply network</p>

*Confirmed against market-leading solution at third-party testing facility.

Technical Specifications

Product Name	Payload	Temperature Range	Duration	Internal Space L x W x H	External Dimensions L x W x H	Tare Weight (with PCM)
Softbox VIP 5L	5 L 0.17 cu ft	+2°C to +8°C	96 hrs	171 x 171 x 168 mm 6.75 x 6.75 x 6.63 in	355.6 x 311.1 x 330.2 mm 14 x 12.25 x 13 in	9.53 kg 21 lbs
			120 hrs			10.9 kg 24 lbs
		+15°C to +25°C	96 hrs			8.8 kg 19.5 lbs
			120 hrs			10.9 kg 22.50 lbs
	4 L 0.14 cu ft	-25°C to -15°C	120 hrs	171 x 171 x 140 mm 6.75 x 6.75 x 5.5 in	381 x 336.55 x 355.6 mm 15 x 13.25 x 14 in	15.9 kg 35 lbs
		< -60°C	120 hrs			4.1 kg 9 lbs
Softbox VIP 8L	8 L 0.28 cu ft	+2°C to +8°C	96 hrs	197 x 197 x 194 mm 7.75 x 7.75 x 7.63 in	381 x 336.55 x 355.6 mm 15 x 13.25 x 14 in	11.3 kg 25 lbs
			120 hrs			13.2 kg 29.10 lbs
		+15°C to +25°C	96 hrs			11.1 kg 24.50 lbs
			120 hrs			12.5 kg 27.50 lbs
		< -60°C	120 hrs			5 kg 11 lbs
			120 hrs			
Softbox VIP 14L	14 L 0.49 cu ft	< -60°C	215 hrs	250 x 250 x 246 mm 9.84 x 9.84 x 9.69 in	533 x 467 x 489 mm 20.98 x 18.38 x 19.52 in	14.9 kg 33 lbs
Softbox VIP 16L	16 L 0.57 cu ft	+2°C to +8°C	96 hrs	248 x 248 x 244 mm 9.72 x 9.75 x 9.63 in	431.8 x 387.35 x 406.4 mm 17 x 15.25 x 16 in	13.8 kg 30.50 lbs
			120 hrs			15.2 kg 33.50 lbs
		+15°C to +25°C	96 hrs			13.2 kg 29.10 lbs
			120 hrs			15.2 kg 33.50 lbs
		-25°C to -15°C	120 hrs			20 kg 44 lbs
			120 hrs			6.6 kg 14 lbs
		< -60°C	120 hrs			
			120 hrs			
Softbox VIP 35L	35 L 1.23 cu ft	+2°C to +8°C	96 hrs	324 x 324 x 324 mm 12.75 x 12.75 x 12.75 in	508 x 463.5 x 482.6 mm 20 x 18.25 x 19 in	20.2 kg 44.50 lbs
			120 hrs			22.9 kg 50.50 lbs
		+15°C to +25°C	96 hrs			20.2 kg 44.50 lbs
			120 hrs			20.9 kg 46 lbs
		-25°C to -15°C	120 hrs			27.7 kg 61 lbs
			120 hrs			10 kg 22 lbs
		< -60°C	120 hrs			
			120 hrs			
Softbox VIP 56L	56 L 1.98 cu ft	+2°C to +8°C	120 hrs	381 x 381 x 381 mm 15 x 15 x 15 in	559 x 502 x 533.5 mm 22 x 19.75 x 21 in	30.4 kg 67 lbs
		-25°C to -15°C				33.1 kg 73 lbs
		< -60°C				17.3 kg 38 lbs



Payload (liters)
5-56



Temperature range
+2°C to +8°C
+15°C to +25°C
-25°C to -15°C
< -60°C



Duration (hours)
96-215+

Contact us at: sales@csafeglobal.com

CSafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. CSafe and the logo designs presented in this material are trademarks or registered trademarks of CSafe. ©2025 CSafe









Proven Excellence in Product Transport

Softbox VIP shippers, featuring vacuum insulated panel technology, provide industry-leading temperature control and versatility, ensuring enhanced peace of mind for your cold chain.

Introducing the Softbox VIP+, the same thermal and mechanical performance of the Softbox VIP, now with an integrated datalogger compartment and a durable containment layer for additional visibility and shipment protection. The Softbox VIP+, when combined with our TracSafe dataloggers and CSafe Connect, provides a complete solution for the safe transport of vital life science products.



Key Features

 <p>High-performance reusable solution</p>	 <p>Qualified against ISTA 7D summer and winter profiles</p>	 <p>Best-in-class VIP insulation for optimal thermal protection</p>	 <p>Industry-leading reuse and requalification program</p>
 <p>Easy to equip for temperature, location, shock, and tilt visibility monitoring</p>	 <p>Durable containment layer for built-in reusability</p>	 <p>Simplified, integrated components reduce the risk of damage during handling</p>	 <p>External datalogger compartment enables ambient and payload temperature monitoring</p>

Technical Specifications

Product Name	Payload	Temperature Range	Duration	Internal Space L x W x H	External Dimensions L x W x H	Tare Weight (with PCM)
Softbox VIP+ 5L	5 L 0.17 cu ft	+2°C to +8°C	120 hrs	171 x 171 x 168 mm 6.75 x 6.75 x 6.63 in	355.6 × 311.1 × 358.8 mm 14 × 12.25 × 14.125 in	11.4 kg 25.0 lbs
		+15°C to +25°C				10.7 kg 23.5 lbs
		-25°C to -15°C				16.0 kg 35.3 lbs
	4 L 0.14 cu ft	< -60°C	120 hrs	171 x 171 x 140 mm 6.75 x 6.75 x 5.5 in	355.6 × 311.1 × 358.8 mm 14 × 12.25 × 14.125 in	10.6 kg 23.3 lbs
Softbox VIP+ 8L	8 L 0.28 cu ft	+2°C to +8°C	120 hrs	197 x 197 x 194 mm 7.75 x 7.75 x 7.63 in	381.0 × 336.6 × 384.2 mm 15 × 13.25 × 15.125 in	13.3 kg 29.3 lbs
		+15°C to +25°C				12.6 kg 27.8 lbs
		< -60°C				12.8 kg 28.3 lbs
Softbox VIP+ 16L	16 L 0.57 cu ft	+2°C to +8°C	120 hrs	248 × 248 × 244 mm 9.72 x 9.75 x 9.63 in	431.8 × 387.4 × 435.0 mm 17 × 15.25 × 17.125 in	16.5 kg 36.3 lbs
		+15°C to +25°C				16.5 kg 36.3 lbs
		-25°C to -15°C				20.9 kg 46.2 lbs
		< -60°C				17.7 kg 38.9 lbs
Softbox VIP+ 35L	35 L 1.23 cu ft	+2°C to +8°C	120 hrs	324 x 324 x 324 mm 12.75 x 12.75 x 12.75 in	508.0 × 463.5 × 511.2 mm 20 × 18.25 × 20.125 in	22.3 kg 49.2 lbs
		+15°C to +25°C				21.6 kg 47.7 lbs
		-25°C to -15°C				27.7 kg 61.1 lbs
		< -60°C				26.4 kg 58.2 lbs



Payload (liters)
5-35



Temperature range
+2°C to +8°C
+15°C to +25°C
-25°C to -15°C
< -60°C



Duration (hours)
120

Contact us at: sales@csafeglobal.com

CSafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. CSafe and the logo designs presented in this material are trademarks or registered trademarks of CSafe. ©2025 CSafe

csafeglobal.com