Thermal Parcels for Low-Risk Lanes

Softbox® ONE parcel shippers provide cost-effective transport of temperature sensitive pharmaceutical products. Tested against challenging standards, you can count on Softbox ONE to protect the integrity of the payload throughout the logistics circuit.



Key Features

- Cost-effective thermal solution
- Tested against challenging standards
- Simple design for quick and easy assembly
- Pre-qualified to meet your needs

SoftboxONE

Technical Specifications

Product Name	Payload	Temperature Range	Duration	Internal Space L x W x H	External Dimensions L x W x H	Tare Weight
Softbox ONE 7	7 L 0.25 cu ft	+2°C to +8°C +15°C to +25°C	72-96 hrs	250 x 214 x 130 mm 9.84 x 8.43 x 5.12 in	475 x 440 x 370 mm 18.70 x 17.32 x 14.57 in	11.5 kg 25.35 lb
Softbox ONE 14	14 L 0.49 cu ft	+2°C to +8°C +15°C to +25°C	72-96 hrs	344 x 264 x 153 mm 13.54 x 10.39 x 6.02 in	564 x 514 x 435 mm 22.20 x 20.24 x 17.13 in	18 kg 39.68 lb
Softbox ONE 28	28 L 0.99 cu ft	+2°C to +8°C +15°C to +25°C	72-96 hrs	385 x 285 x 250 mm 15.16 x 11.22 x 9.84 in	632 x 532 x 505 mm 24.88 x 20.94 x 19.88 in	20.5 kg 45.19 lb
Softbox ONE 65	65 L 2.29 cu ft	+2°C to +8°C +15°C to +25°C	72-96 hrs	600 x 400 x 290 mm 26.63 x 15.75 x 11.42 in	860 x 650 x 540 mm 33.86 x 25.59 x 21.26 in	31 kg 68.3 lb

Specified measurements are subject to minor variation due to rounding and unit conversion between metric and imperial system.

Payload (liters)
7-65

Temperature range
+2°C to +8°C
+15°C to +25°C

Duration (hours)
72-96

Contact us at: sales@csafeglobal.com

CSafe has a global network of service centers, stations, supply points and team members to provide support and solutions where and when you need them. CSafe and the logo designs presented in this material are trademarks or registered trademarks of CSafe. ©2026 CSafe

csafeglobal.com